Donaldson
FILTRATION SOLUTIONS

Product Specifications



P553191

LUBE FILTER, SPIN-ON FULL FLOW

About Donaldson P553191

The P553191 is designed to maintain oil cleanliness and protect engines from wear-causing contaminants. It captures impurities that accumulate during operation, supporting extended oil life and efficient lubrication while delivering cleaner fluids to your engine components. Built with durable components and tested for consistent filtration performance, it provides dependable protection across a wide range of operating conditions.

Attributes

Outer Diameter	108 mm (4.25 inch)
Thread Size	1 1/8-16 UN
Length	262 mm (10.31 inch)
Gasket OD	99 mm (3.90 inch)
Gasket ID	90 mm (3.54 inch)
Efficiency 99%	21 micron
Efficiency Test Std	ISO 16889
Media Type	Cellulose
Collapse Burst	10.3 bar (149 psi)

Type	Full-Flow
Style	Spin-On
Primary Application	up to EURO4 applications, for EURO5/6 use P551807

Other Information

UPC Code	742330044308

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.

© Donaldson Company, Inc.